



Aviation Technical Bulletin

Route to:SERVICE
MANAGERSALES
MANAGERBULLETIN
BOARD

March, 1987

No. 87-4

Supersedes 75-2

PROPER USE OF THE CHAMPION CT-470 CAN CUTTER

TO PREVENT DAMAGING OF THE CUTTER WHEEL ON THE CHAMPION CT-470 OIL FILTER CAN CUTTER, PLEASE ADHERE TO THE FOLLOWING INSTRUCTIONS:

1. This oil filter can cutter is used in the same manner as a standard copper or aluminum tube cutter. It should never be used like an ordinary kitchen can opener.
2. When cutting open either a male or female filter, always make certain the filter is screwed all the way down until it bottoms on the threaded adapter or the rotated bushing.
3. Always turn the filter or can cutter clockwise.
4. Tighten the knurled head screw until cutter wheel meets the metal can. Rotate filter or can cutter 360°. Again, slightly tighten knurled screw and repeat the rotating action 360°. To completely cut the can open, it usually takes three or four cycles of this procedure.

REPLACEMENT CUTTER WHEELS, PART NO. CT-470-4, ARE AVAILABLE THROUGH YOUR CHAMPION DISTRIBUTOR.

Champion Aviation Products: Your Blueprint for Performance

JTQ:mf